

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in this application.

Listing of Claims:

1. (original) Eyewear comprising:

a first lens and a second lens;

a frame with a half-jacket frame front adapted to receive the first lens and the second lens; and

a removable shield for reducing direct impingement of moving unfiltered air and dust on a wearer's eye, the removable shield configured to extend from the half-jacket frame front to the wearer's face and having two lens openings,

wherein the removable shield forms a first tunnel between the first lens and the wearer's first eye and a second tunnel between the second lens and the wearer's second eye.

2. (original) The eyewear of claim 1, wherein the removable shield has a uniform thickness.

3. (original) The eyewear of claim 2, wherein the uniform thickness is about one quarter inch.

4. (currently amended) The eyewear of claim 1 wherein the half jacket frame front is rigid and cast in one piece from a metal comprising titanium.

5. (currently amended) The eyewear of claim 1 wherein the shield further comprises a rigid plastic portion and a foam portion attached thereto, the foam portion comprising air-permeable foam, the rigid portion adapted to be seated against a

rearward face of the half jacket frame and the foam portion adapted to contact the wearer's face when the eyewear is in use.

6. (original) The eyewear of claim 1, further comprising a vent configured to reduce fogging of the lens.

7. (original) The eyewear of claim 6, wherein the vent is formed in the half-jacket frame front.

8. (original) The eyewear of claim 6, wherein the vent is formed in the removable shield.

9. (original) The eyewear of claim 1, wherein the eyewear is vent-free.

10. (original) The eyewear of claim 1, further comprising substantially rigid temples.

11. (original) The eyewear of claim 10, further comprising slip resistors carried by the temples.

12. (original) The eyewear of claim 11, wherein the slip resistors are permanently affixed to the temples with an adhesive.

13- 30. (canceled)

31. (new) Eyewear comprising:

a first orbital and a second orbital;

a first lens and a second lens disposed respectively in the first and the second orbital, a connecting bridge between said orbital;

said first and second orbital extending respectively over upper portions of said first and said second lens so as to form a half jacket from a said half-jacket frame front adapted to receive the first lens and the second lens;

a removable shield for reducing direct impingement of moving unfiltered air and dust on a wearer's eye, the removable shield configured to extend from the half-jacket frame front to the wearer's face and configured to seal the frame front to a wearer's face when in use to prevent direct impingement of air and dust from outside the eyewear on the wearer's eyes, said shield having two lens openings,

the removable shield forming a first tunnel between the first lens and the wearer's first eye and a second tunnel between the second lens and the wearer's second eye, and

shield retainer means, said shield retainer means being substantially hidden when the shield is removed.

32. (new) The eyewear of claim 31 further including a shield retainer carried by the nose contacting element, the nose contacting element having:

a nosepad extending rearwardly from the half jacket frame; and

a nosepad cover at least partially covering the nosepad.

33. (new) The eyewear of claim 32 wherein the shield retainer carried by the nose-contacting element is the sole means of attachment provided for a shield.

34. (new) The eyewear of claim 31, further comprising:

a substantially rigid temple comprising temple gripping means for a person to grip the temple, the temple gripping means being substantially hidden when the goggles are worn, the temple gripping means comprising an arcuate thumb-shaped indentation formed in the temple.

35. (new) The eyewear of claim 31 wherein each orbital of the half-jacket frame has formed therein a lens-retaining groove defined by at least one lens-retaining ridge running from left to right along the half-jacket frame, the lens-retaining ridge having at least one long run measuring about one inch from left to right along the half-jacket frame front, the long run of the lens-retaining ridge having a cross-sectional dimension averaging less than about 0.6 millimeters.

36. (new) The eyewear of claim 35 wherein the lens-retaining ridge has at least one short run measuring one-half inch from left to right along the half-jacket frame, the short run of the lens-retaining ridge having a cross-sectional dimension averaging no more than about 0.3 millimeters.

37. (new) The eyewear of claim 35 wherein the lens-retaining ridge comprises titanium.